



磐亞股份有限公司

PAN ASIA CHEMICAL CORPORATION

100台北市中正區新生南路一段50號11樓

11F, No. 50, Sec. 1, Hsin Sheng South Rd., Taipei, 100 Taiwan

Tel:+886-2-2351-1212 Fax:+886-2-2396-2946 <http://www.pacc.com.tw> E-mail:paccsale@pacc.com.tw

Technical Data Sheet

品名 (trade name)	PANNOX PEG 600T
CTFA name	聚乙二醇 polyethylene glycol
外觀 appearance 25°C	無色透明液體 transparence colorless liquid
PH(5% aq)	4.0~7.0
含水量 water content %	0.5 max
色度 color(apha)	40 max
氫氧價 OHV(mg KOH/g)	178 ~ 196
平均分子量 Average molecular weight	570 ~ 630
包裝 packing	230 kg /iron drum

用途 Applications :

造紙業潤濕劑及分散劑，橡膠業離型劑，化粧品及製藥業及木材保濕劑、PU 合成、酯化原料。

It is used for wetting agent in paper industry and excellent lubricant and mold releasing agent in rubber. It also extensively used in cosmetic . pharmacy and timber for keep moisture. PU synthetic .Besides , as the PU synthetic and esterification materials .