



PAN ASIA CHEMICAL CORPORATION

Tel:+886-2-2351-1212 Fax:+886-2-2396-2946

http://www.pacc.com.tw E-mail:paccsale@pacc.com.tw

**2-ETHYLHEXYL ALCOHOL POLYETHYLENE GLYCOL ETHER**

Trade Name	Hydrophobic	EO mole	water% (max)	PH value (1% aq)	Color(40°C) APHA (max)	FORM in 25°C	C.P °C 1% aq	HLB	OHV mg KOH/g	Applications產品應用範圍
PANNOX 402	2-ethylhexyl alcohol	2.0	0.5	5.5-7.5	60	L	○ 49.5-51.5	8.1		皮革塗層滲透劑, 可作脫脂劑 電鍍行業中用作光亮助劑 Leather coating penetrant, also for degreasing agent. used as a light aid.
PANNOX 402B	2-ethylhexyl alcohol	2.5	0.5	5.5-7.5	60	L/S	○ 59-63	9.2		
PANNOX 403	2-ethylhexyl alcohol	3.0	0.5	5.5-7.5	60	L/S	○ 69.5-73.5	10.1		
PANNOX 407	2-ethylhexyl alcohol	7.0	0.5	5.5-7.5	60	L/S		14.0	123-133	
PANNOX 410	2-ethylhexyl alcohol	10	0.5	5.5-7.5	60	S		15.4	97-103	
PANNOX 410PAB	2-ethylhexyl alcohol		0.5	5.0-7.0	60	L		12.8	96-106	
PANNOX 413	2-ethylhexyl alcohol	13	0.5	5.5-7.5	60	S		16.3	75-85	
PANNOX 415A	2-ethylhexyl alcohol	15	19-21	6.0-8.0	60	L	@ 73.5-77.5	16.7		
PANNOX 415	2-ethylhexyl alcohol	15	0.5	5.5-7.5	60	S	@ 73.5-77.5	16.7	68-74	

L = liquid S= solid L/S = liquid&amp;solid